

AUTOMATIC CHILLER + CARBONATOR

AQUAMIX 1 Top / Under

Domestic equipment for the treatment of drinking water compliant with the Ministry of Health Decree No. 443 of 21/12/1990

AQUAMIX 1 (in the Top and Under versions) is a compact, automatic, high-performance system for domestic use that dispenses cold, sparkling and ambient temperature water. AQUAMIX 1 Top is the only unit equipped with a front compartment for housing the frontal purification filter (optional) and an easily accessible CO₂ cylinder, allowing for very simple user maintenance.

It features quick and simplified push-fit connectors for easy over-sink installation.

The AQUAMIX 1 Under version, with the same performance, is designed for under-sink installation.

STANDARD EQUIPMENT

- High efficiency with a dispensing capacity of 19 litres/hour of cold and sparkling water (at 20 °C)
- Digital control and multi-function display for managing dispensing temperature, carbonation system diagnostics, and filter wear
- Automatic filling function setting easily programmable for a single glass or a carafe
- AISI 304L stainless steel front panel
- Maximum quietness of the refrigeration system: only 32 dB in operation.
- Installation kit



AQUAMIX 1 Top

AQUAMIX 1 TOP TECHNICAL DATA

Power Supply (voltage / frequency)	230 V CA - 50 Hz
Absorption (Watts / Amperes)	0.94 A* / 1.35 A**
Refrigerant Gas	HFC 134A
Dimensions (l x p x h -cm) - Weight (Kg)	38,5 x 24 x 32,5* - 21* / 25** Kg

AQUAMIX 1 TOP COOLING CAPACITY

Litres of cold water per hour at 18 °C	19* / 28**
200 CC glasses of cold water per hour	95* / 140**

*chiller + ambient temp/**chiller + ambient temp + carbonator

ACCESSORIES

- Filtration and dechlorination system with U.V. sterilizer
- Reverse Osmosis purification system
- Additional faucet for ambient temperature water, 3-way and 5-way
- Pre-filtration cartridge - 26 x 14 cm
- Disposable cylinder - 26 x 7 cm
- Refillable cylinder (for AQUAMIX1 Under) - 58 x 14 cm



AQUAMIX 1 Under



AQUAMIX 1 UNDER TECHNICAL DATA

Power Supply (voltage / frequency)	230 V CA - 50 Hz
Absorption (Watts / Amperes)	240 W / 0.75* / 0.65**
Refrigerant Gas	HFC 134A
Dimensions (l x p x h -cm) - Weight	30 x 24 x 52* / 47** - 23* / 24** Kg

AQUAMIX 1 UNDER COOLING CAPACITY

Litres of cold water per hour at 18 °C	19
200 CC glasses of cold water per hour	95

*chiller + ambient temp/**chiller + ambient temp + carbonator