

CHILLERS + CARBONATORS

AquaMIX and AquaMIX 1 is a compact automatic system without accumulation tank with high performance that dispenses fresh, sparkling and room temperature water. AquaMIX 1 Top is equipped with front compartment for housing the purification filter (optional) and CO2 bottle for very simple maintenance. It has quick-connect fittings for simple over-sink installation. AquaMIX 1 Under, with the same performance, is prepared

for under-sink installation. Refrigeration occurs inside the system with water passing through a cooling coil. The electronic thermostat with display allows regulation of the desired temperature and instant dispensing of cold and carbonated water. Maximum silence, with chromed brass taps for food use, ecological gas without CFC and integral closure of the container.



AQUAMIX TOP



AQUAMIX UNDER

AQUAMIX 1 TOP



AQUAMIX 1 UNDER

TECHNICAL DATA

	AQUAMIX 1 TOP	AQUAMIX 1 UNDER
Power Supply (voltage/frequency)	230V AC - 50 Hz	230V AC - 50 Hz
Power consumption (Watt/hour)	0.7 A* / 1.2 A**	0.7 A* / 1.2 A**
Type of refrigerant gas	HFC 134A	HFC 134A
Dimensions (W x D x H - cm) - Weight (Kg)	25 x 54 x 47 - 19* Kg 35 x 50.5 x 44 - 25** Kg	25 x 44.5 x 41 - 17* Kg 35 x 50.5 x 44 - 25** Kg

*cooler + room temp. + carbonator

**bar cooler + room temp. + carbonator

COOLING CAPACITY

Liters of cold water per hour at 18°C	45* / 65**	65
---------------------------------------	------------	----

*cooler + room temp. + carbonator

**bar cooler + room temp. + carbonator